



CAMERA

TD-9420S4L-C

2MP Dual Illumination Water-proof
Bullet Network Camera



- H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- Max. resolution: 2MP (1920 × 1080)
- Auto day/night switch
- 3D DNR, WDR, HLC, BLC, etc.
- ROI coding
- Support smart supplement light
- 10~20m white light view distance; 10~20m IR view distance
- DC12V/PoE power supply
- IP 67 ingress protection
- Support dual streams
- Support remote monitoring by smart phones& tablet PCs with iOS and Android OS
- Support line crossing detection & region intrusion detection
- Support SMD



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay
Eco-Technology Park, Nanshan District, Shenzhen, Guangdong
Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: overseas@tvt.net.cn

SPECIFICATIONS

Specifications	Model	TD-9420S4L-C		
Camera				
Image Sensor		1 / 3 "CMOS		
Image Size		1920×1080		
Electronic Shutter		1 / 3s ~ 1 / 100000s		
Iris Type		Fixed Iris		
Min. Illumination		0.02 lux @F2.2, AGC ON; 0 lux (Illumination on)		
Lens		2.8mm@F2.2, Horizontal FoV: 95°; Vertical FoV: 55°; Diagonal FoV: 109° 3.6mm@F2.2, Horizontal FoV: 75°; Vertical FoV: 41°; Diagonal FoV: 86°		
Focus		Fixed		
Lens Mount		M12		
Day&Night		ICR		
Wide Dynamic Range		Digital WDR		
BLC		Yes		
HLC		Yes		
Digital NR		Yes		
S/N Ratio		≥50dB		
Angle Adjustment		Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°		
DORI Distance				
Lens	Detect	Observe	Recognize	Identify
2.8mm	41m(133ft)	17m(55ft)	8m(26ft)	4m(13ft)
3.6mm	58m(190ft)	23m(75ft)	12m(39ft)	6m(19ft)
Image				
Video Compression	Main stream: H.265+ / H.265 / H.264 + / H.264 Sub stream: H.265+ / H.265 / H.264 + / H.264 / MJPEG			
H.265 Compression Standard	Main Profile@Leve4.1 High Tier			
Resolution	1080P (1920×1080), 720P(1280×720), D1, VGA(640×480), 480×240, CIF			
Main Stream	1080P/720P(60Hz: 1~30fps; 50Hz: 1~25fps)			
Sub Stream	D1/VGA/480×240/CIF (60Hz: 1~30fps; 50Hz: 1~25fps)			
Bit Rate	64 Kbps ~ 3 Mbps			
Bit Rate Type	VBR / CBR			
Audio Compression	G711A/U			
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
Interfaces				
Network	RJ45			
Video Output	No			
Audio	1CH built-in MIC			
Storage	No			
Reset	No			
Functions				
Remote Monitoring	Web browser / TVT NVR/NVMS2.X/Mobile APP			
Web Browser	IE 11 (plug-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+			
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission			
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, 802.1x, HTTP			
Interface Protocol	ONVIF			
Storage	Network remote storage			
Motion Detection	Support smart motion detection; filtering motion alarm triggered by other target types except humans.			
Smart Event	(Human) region intrusion detection, (human)line crossing detection			
General Function	Watermark, video mask, heartbeat, corridor pattern			
Security	Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP			

PoE	Yes, IEEE802.3af
Supplement Light Range	IR range: 10 ~ 20 m; white light range: 10 ~ 20 m
Ingress Protection	IP67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 5W
Operating Environment	- 20 °C ~ 55 °C (-4°F~131°F); Humidity: less than 95 % (non-condensing)
Storage Environment	- 20 °C ~ 60°C (-4°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	162.1 × 74.8 × 73.8
Weight (net)	Approx. 0.25KG
Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9420S4L-C(D/PE/AW1)
-----------------	------------------------