

# 4POE+2FE 5 PORT POE Switch (Built-in 52V 1.5A Power Adapter)



- ✧ 4\*10/100mbps POE port, 2\*10/100mbps UP Link port
- ✧ 100m Distance; Vlan supported
- ✧ Power Pins:45+78-
- ✧ Data Pins:1236
- ✧ Input: 52V 1.5A
- ✧ Output:78W(52V 1.5A)
- ✧ Each port max. power supply reached 30W.

## Application:

- ✧ Wireless Access Point
- ✧ IP Camera
- ✧ IP Phone
- ✧ Computer Networks

Product	4+2 Port Passive POE Switch (52V 1.5A)
Model	Hi-SF0420FB4L
POE Port	1 to 4 Supply Power
Up Link Port	2 Port
Power Pin	4/5+7/8-
Whole Power	≤78W(52V 1.5A)
Input Power	52V 1.5A
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3、IEEE802.3u、802.3x、802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port 100BASE-tx: 14800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working temperature: -10° -- 55° C
Weight	0.92kg
Size	200×119×40mm