

## DH-HAC-HDW2200S

2Megapixel 1080P Water-proof IR HDCVI Mini Dome Camera



### Features

- 1/3" 2Megapixel CMOS
- 25/30fps@1080P, 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switch
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR,
- 3.6mm fixed lens (2.8 mm, 6mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V


## DH-HAC-HDW2200S

### Technical Specifications


Model	DH-HAC-HDW2200SP	DH-HAC-HDW2200SN
<b>Camera</b>		
Image Sensor	1/3" 2Mega CMOS	
Effective Pixels	1920(H)×1080(V)	
Electronic Shutter	1/3s~1/100,000s	
Video Frame Rate	1920×1080@25 fps; 1920×1080@30 fps; 1280×720@25 fps; 1280×720@30 fps; 1280×720@50 fps; 1280×720@60 fps	
Synchronization	Internal	
Min. Illumination	0.05Lux@F1.2(0Lux IR LED on)	
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)	
<b>Camera Features</b>		
Max. IR LEDs Length	20m, Smart IR	
Day/Night	Auto(ICR)/B&W/Color	
Noise Reduction	3D/2D	
OSD Menu	Support	
<b>Lens</b>		
Focal Length	3.6mm (2.8mm, 6mm, 8mm optional)	
Mount Type	M12	
<b>General</b>		
Power Supply	DC12V±10%	
Power Consumption	Max 3.5W	
Working Environment	-30°C~+60°C/ Less than 95%RH (no condensation)	
Transmission Distance	Over 300m via 75-3 coaxial cable	
Ingress Protection	IP66	
Dimensions	Φ113.6mm x 85.8mm	
Weight	300g	

# DH-HAC-HDW2200S

## Dimensions (mm)



## Accessory (optional)



### Securitem Ltd.

Via Sant'Agostino, 13  
20811 Cesano Maderno (MB) - Italy  
Tel: +39-0362-1855440  
Fax: +39-02-45503999  
Email: info@setik.biz  
www.setik.biz

\*Design and specifications are subject to change without notice.

© Dahua Technology Co., Ltd.