

# 24+2+2 Port 400W POE Switch (Built-in)



- ✧ 24\*10/100mbps POE port;2\*10/100/1000mbps UP Link;  
2\*10/100/1000mbps SFP
- ✧ 100m Distance
- ✧ Support IEEE802.3AF/AT
- ✧ Whole Power:400W(52V 7.7A)
- ✧ All port supported by MDI/MDIX auto flip and self negotiation
- ✧ Supply 28\*10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- ✧ Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- ✧ Each port max. power supply reached 30W.

## Application:

- ✧ Wireless Access Point
- ✧ IP Camera
- ✧ IP Phone
- ✧ Computer Networks

Model	24+2+2 port 400W POE switch(Built-in)
Model No.	Hi-F2422GB
PoE Port	1 to 24 port support 100mbps IEEE802.3af/at
UP link port	25 <sup>th</sup> -28 <sup>th</sup> port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤400W(52V 7.7A)
PoE type	End-span
Power distance	≤150m
Network Standard	IEEE 802.3、IEEE802.3u、802.3x、802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤150m
Switch capability	12.8Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps 1000Mbps:14800pps
MAC Address	16K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	LINK/ACT. 100Mbps;POE Status indicator; POWER indicator
Working Environment	Working Temperature: -10° -- 55° C
Input power	AC100-240V 50/60HZ
Weight	4.2kg
Size	440mm*285mm*44mm (L*W*H)