

8+2+2 Port Full Giga AI POE Switch



- ✧ 8*100/1000Mbps POE port; 2*100/1000Mbps UP Link port; 2*100/1000Mbps SFP Port
- ✧ 100m Distance
- ✧ Support IEEE802.3AF/AT
- ✧ Whole Power:120W(52V 2.3A)
- ✧ 12 36 pin supply power; 12 36 and 45+78- supply data
- ✧ All port supported by MDI/MDIX auto flip and self negotiation
- ✧ Supply 11*10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- ✧ Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- ✧ Each port max. power supply reached 30W.

Function:

- ✧ **AI Watchdog**
- ✧ **AI QOS**
- ✧ **AI 1000Mbps Vlan protection**

Product	8+2+2 Port full giga AI POE Switch
Model	Hi-G0822GB
POE Port	1 to 8 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+、 3/6- and 4/5+7/8-
Whole Power	≤120W (52V 2.3A)
POE Type	End-span
Power Distance	≤200m
Network Standard	IEEE 802.3、 IEEE802.3u、 802.3x、 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps 1000Mbps:14800pps
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	Each port occupied 1 LINK/ACT.100Mbps, POE Status Indicator, Whole power indicator
Working Environment	Working temperature: -10°-- 55°C
Input	AC110-240V 50/60HZ
Weight	1.8kg
Size	270mm*180mm*44mm(L*W*H)